

mafdel		Bottom side	Top side	Embossing on top side	Maximum width (mm)	Thickness (mm)						
						1	1.5	2	2.5	3	4	5
DEL/ROC	100 ShA 55 ShD	Smooth	Smooth	No	650							
DEL/ROC	100 ShA 55 ShD	Smooth	Smooth	No	1000							
DEL/ROC	100 ShA 55 ShD	Diamond-embossed	Smooth	No	1000							
DEL/FLEX	93 ShA	Smooth	Smooth	Yes	650							
DEL/FLEX	93 ShA	Smooth	Smooth	Yes	650							
DEL/FLEX	93 ShA	Smooth	Smooth	Yes	1000							
DEL/FLEX	93 ShA	Diamond-embossed	Smooth	Yes	1000							
DEL/FLEX	93 ShA	Reinforcement ply	Smooth	Yes	1000							
SOUPLEX	85 ShA	Smooth	Smooth	Yes	650							
SOUPLEX	85 ShA	Smooth	Smooth	Yes	650							
SOUPLEX	85 ShA	Smooth	Smooth	Yes	380							
TOTALGRIP Surface	70 ShA	Smooth	Smooth	Yes	380							
Special PRIMAFLEX	90 ShA	Smooth or Brushed	Smooth	Yes	380							

DEL/ROC, DEL/FLEX and SOUPLEX conveyor belts with guides on demand



Possible embossings on DEL/FLEX and SOUPLEX conveyor and flat belts: non-slip studded, sawtooth, SG3 or diamond. Maximum width: 380 mm.



non-slip studded (PI)



sawtooth (US)



SG3 (SG)



diamond (LO)