

∅ mm

		mafdel		2	3	4	5	6	7	8	9	9.5	10	12	12.5	15	18	
Standard	Rough	POLY/FLEX Rough	85 ShA	●	●	●	●	●	●	●	●		●	●		●	●	
		POLY/FLEX Rough	85 ShA		●	●	●	●		●				●	●			
	Smooth	SOUPLEX	85 ShA		●	●	●	●			●		●			●	●	●
		SOUPLEX	85 ShA		○	○	○	○			○							
		SOUPLEX Antistatic	85 ShA			●	●	●										
		DEL/FLEX	90 ShA	●	●	●	●	●	●	●	●		●			●	●	●
		DEL/FLEX	90 ShA		●	●	●	●			●							
		DEL/ROC	100 ShA 55 ShD			●	●	●			●		○	●				
	Frosted	SOUPLEX Frosted	85 ShA						●		●		●			●	●	●
		DEL/FLEX Frosted	90 ShA						●	●	●		●			●	●	●
		DEL/FLEX Frosted	90 ShA						●		●							
	Reinforced	Smooth	POLY/FLEX Aramid Reinforced	85 ShA					●		●			●	●		●	●
DEL/SAN Aramid Reinforced			95 ShA											●		●	●	●
DEL/ROC Polyester Reinforced			100 ShA 55 ShD										○	○		○	○	○
DEL/ROC «DRW» Polyester Reinforced			63 ShD										○		○			
Frosted		POLY/FLEX Aramid Reinforced - Frosted	85 ShA						●		●			●	●		●	●
		DEL/SAN Aramid Reinforced - Frosted	95 ShA												●		●	●
Tubular	SOUPLEX Tubular	85 ShA											○					
	DEL/FLEX Tubular	90 ShA					○	○		○			○	○		○		



All our 6 to 18mm diameter round belts can be frosted. Frosting improves belt sliding on its support and makes products accumulation easier.



Patent nb 9912595