

mafdel			w x h mm									
			6 x 4 (Y)	8 x 5 (M)	10 x 6 (Z)	13 x 8 (A)	17 x 11 (B)	22 x 14 (C)	32 x 19 (D)	13 x 15 (A)	17 x 20 (B)	22 x 25 (C)
Standard	Non-reinforced	DEL/ROC 100 ShA 55 ShD										
		DEL/FLEX 90 ShA										
		DEL/FLEX 90 ShA										
		SOUPLEX 85 ShA										
		SUPERFLEX 70 ShA										
	Reinforced	DEL/SAN Aramid reinforced 95 ShA										
		H15 / H16 Aramid reinforced 92 ShA										
		SOUPLEX Aramid reinforced 85 ShA										
	Ridge-Top	Standard	DEL/FLEX 90 ShA									
SOUPLEX Aramid reinforced 85 ShA												
TOPGRIP		DEL/FLEX 90 ShA										
		SOUPLEX 85 ShA										
		DEL/SAN Aramid reinforced 95 ShA										
		H15 / H16 Aramid reinforced 92 ShA										
		SOUPLEX Aramid reinforced 85 ShA										



All V belts from 10 x 6 mm (Z) section can be cogged.
Cogging reduces minimum pulley diameter.



10 x 6
13 x 8



17 x 11
22 x 14
32 x 19



Coatings : from 10 x 6mm (Z) section
Wide range of smooth or textured coatings made of
PU, PVC, felt, rubber.